

# Case IH JXU Series

**POWER FARMING**  
520 Elizabeth Street Melbourne 3000 [www.powerfarming.com.au](http://www.powerfarming.com.au)

	JXU 75	JXU 85	JXU 95	JXU 105
<b>ENGINE</b>				
No. of cylinders / capacity [cm <sup>3</sup> ] / type	4 / 4500 / Turbocharged and Intercooled			
Rated engine power ECE R120 @ 2,300rpm [kW/hp[CV]]	56 / 76	63 / 86	71 / 97	78 / 106
Max torque ECE R120 @ 1,400rpm [kW/Hp[CV]]	324	366	404	425
Torque rise acc. OECD [%]	39	40	37	31
Fuel tank capacity - standard / optional [litres]	127 / -	127 / -	127 / 167	127 / 167
<b>TRANSMISSION</b>				
Type Powershuttle	24 Fwd / 24 Rev with 2 speed powershift and powershuttle			
Type Optional [Optional with creeper]	12 Fwd / 12 Rev [20 Fwd / 12 Rev] with mechanical shuttle			
<b>DRIVE and STEERING</b>				
4wd front axle standard	electro-hydraulic engagement with limited slip differential lock			
4wd optional feature	electro-hydraulic fully locking differential			
Turning radius 2wd / 4wd [mm]	3770 / 4050	3770 / 4050	3770 / 4050	3770 / 4050
<b>POWER TAKE OFF</b>				
Type	electro-hydraulic engagement			
Rear speeds available	540 / 540E / 1000 rpm + Proportional Ground Speed			
Front pto	1000 rpm			
<b>HYDRAULIC SYSTEM</b>				
Max pump flow - steering / hitch and external services	36l/min / 61l/min (optional 80l/min combined flow system)			
Remote valves	max 3 rear and 2 mid mounted Closed Centre type			
Control type	EHC [Electronic Hitch Control] or MHC [Mechanical Hitch Control]			
Rear lift Capacity - standard / optional [kg]	3900 / 4900	3900 / 4900	4900 / 5850	4900 / 5850
Front hitch lift capacity [kg]	2500	2500	2500	2500
<b>WEIGHT and DIMENSIONS</b>				
Minimum weight* [kg]	3750	3750	3890	3890
Permissible total weight* [kg]	6200	6500	6800	6800
Max length [mm]	4120	4120	4120	4120
Min / Max track width [mm]	1425 / 2133	1425 / 2133	1425 / 2133	1425 / 2133
Max height standard cab / low roof cab [mm]	2595 / 2511	2595 / 2511	2620 / 2536	2620 / 2536
Max height over ROPS folded / unfolded [mm]	2174 / 2716	2174 / 2716	2199 / 2741	2199 / 2741
Wheelbase - 2wd / 4wd [mm]	2342 / 2350	2342 / 2350	2342 / 2350	2342 / 2350
<b>STANDARD TYRES</b>				
Front 2wd / 4wd	9.00-16 / 12.4 R 24	9.00-16 / 12.4 R 24	10.00-16 / 380/70 R24	10.00-16 / 380/70 R24
Rear	18.4 R 30	18.4 R 30	480 / 70 R 34	480 / 70 R 34

(\* ) to comply with legislation and specification in your country 1) ECE R-120 correspond to ISO TR14396 2) With Standard tyres 3) Other tyre options on request ● Standard ○ Optional at extra cost - Not available